product details

LUNETTA LED

Product description:	LUNETTA LED
Product code:	4050300952505
Quantity:	Blister (BLI) contains 1 Piece (PCE)

You can find this product in the eCatalog:
http://catalog.myosram.com?~language=EN&~country=COM&it_p=4050300952505

Applications	
Dimmable	No
With on/off switch	No
Adjustable	Yes
Type of connection	FLAT CONNECTOR
Type of cover	PRISMATIC

Categorizations	
SEG number	9452350
Sstl-Number	4107727

Certificates & Standards	
Standards	CE; ENEC10 VDE
Protection against ignition and fire	F
Protection class	II
Type of protection	IP20

General Description	
Number of lighting outlets	1
Equipment	LED
Reflector type	POLISHED
Recycling	Yes
Body material	PC241/RED.HEAD: ABS PA757
Reflector material	POLYCARBONATE METALLISED

Technical - Colors	
Product color	WHITE

Technical - Electrical Data	
Nominal wattage	0.45 W
Nominal voltage	220-250 V
Mains frequency	50 Hz
Nominal current	0.04 A

Technical - Geometries	
Diameter	50 mm
Length	85.00 mm
Width	50.00 mm
Height	50.00 mm

Packaging units

Product code	Packaging type and content	Dimensions in h x w x l	Gross weight	Volume
4050300952505	Blister contains 1 Piece	95,000 mm x 85,000 mm x 135,000 mm	55,600 g (0,000 g)	1,011 Cubic dec.

Subject to change without notice. Errors and omission excepted.
© 2011 OSRAM GmbH

product details

LUNETTA LED

Packaging units				
Product code	**Packaging type and content**	**Dimensions in h x w x l**	**Gross weight**	**Volume**
4050300792316	Shipping carton box contains 20 Piece	222,000 mm x 146,000 mm x 410,000 mm	1.354,286 g (0,000 g)	12,808 Cubic dec.

LUNETTA LED

LUNETTA LED is an orientation light with an euro-plug. The integrated sensor controls the luminaire according to light, and the 360° rotatable head allows an optimum light control. The prismatic cover ensures the light is distributed evenly.

- Brightness sensor for automatic operation
- Rotary head (360°)
- Prismatic cover to distribute the light evenly
- Equipped with yellow LED
- CE Sign ENEC 10 Sign VDE Sign F Sign Protection class 2 sign IP20, 220-250 V, 50-60 Hz

Subject to change without notice. Errors and omission excepted.
© 2011 OSRAM GmbH